

SPECIFICATIONS

	1650 Discovery Tiller	
Overall Length	16' 6"	5.03 m
Boat/Motor/Trailer Length	21' 6"	6.55 m
Boat/Motor/Trailer Width	6' 4"	1.93 m
Boat/Motor/Trailer Height	5' 9"	1.75 m
Beam	75.5"	1.92 m
Chine Width	58"	1.47 m
Max Depth	33.5"	85 cm
Max Cockpit Depth	21.5"	55 cm
Transom Height	20"	51 cm
Deadrise	6°	
Weight (Boat only, dry)	835#	379 kg
Max Weight Capacity	1,250#	567 kg
Max Person Capacity	5	
Max HP Capacity	60	
Fuel Capacity	Portable	
Aluminum Gauge Bottom	.090"	
Aluminum Gauge Sides	.080"	
Aluminum Gauge Transom	.100"	



STANDARD FEATURES

Console/Instrumentation

- Console, starboard, rocker switches, 2 drink holders, phone storage, & 12V power outlet (SC only)
- Steering wheel, black (SC only)
- No-feedback steering (SC only)
- Switch panel w/circuit breakers
- Master power switch

Flooring

- Carpet, 16 oz. marine-grade, w/Limited Lifetime Warranty treated panel

Seating

- Seat, Deluxe w/fixed pedestal base (1)
- Seat, Deluxe w/pedestal (1)
- Pedestal floor bases (4) (Tiller only)
- Pedestal floor bases (5) (SC only)

Storage/Convenience

- Storage cubby (foredeck)
- Storage compartments (port and starboard, bow)
- Storage, open (under starboard platform, bow)
- Storage, open (port and starboard cockpit)
- Storage compartment, battery & portable fuel tank (port, stern)
- Storage compartment (can fit 2nd portable fuel tank) (starboard, stern)
- Trolling motor battery storage compartment (12V system compatible) (bow)

Rod Storage

- Rod rack, quick access system (port) (2 rods @ 9' capacity)
- Rod rack, quick access system (starboard) (2 rods @ 9' capacity) (Tiller only)
- Rod storage (center, lockable, in-floor) (4 tubes @ 8'6" capacity)

Livewells/Baitwells

- Livewell, 11 gal. aerated (bow) (33.5Lx9.5Wx8D)

Interior Features

- Bilge pump (manual)
- Lanyard, ignition stop switch
- Level flotation
- Light, navigation

Exterior Features

- Transom, wood-free
- Hull, 4 piece aluminum all-welded, variable degree deadrise
- Keel, extruded full length, welded (center)
- Reverse chine extrusion, welded full length w/spray deflector
- Gunnel, extruded w/SureMount & J-Hook systems
- Corner caps, formed (stern)
- Paint process, baked Armor-Guard
- Cleats, black composite (4)
- Reboarding ladder
- Eyes, stainless steel (bow & stern)

STANDARD PAINT OPTIONS

